

Professional digital multimeters True RMS

PAN 188

Digitalmultimeter True RMS 1000V CAT III with Bluetooth and USB interface

- True RMS measurement
- Android app
- LCD display with bargraph
- Digital Display 21 mm
- Backlight
- Automatic and manual range selection
- Diode test
- Min / Max memory
- Data Hold
- Relative mode (REL)
- Transistor test
- Auto power off

Scope of delivery: Operating manual, test leads, Type-K temperature probe, protective cover, Bluetooth PC interface + software, Battery(s) not included



Technical Data	PAN 188
DC voltage (V =)	0,01 mV - 1000 V
AC voltage (V ~)	0,01 mV - 750 V
DC current (A =)	0,1 µA - 10 A
AC current (A ~)	0,1 µA - 10 A
Resistance (Ω)	0,1 Ω - 60 MΩ
Continuity test (•)))	< 50 Ω
Frequency (Hz)	0,01 Hz - 10 MHz
Duty-cycle	0,1 - 99,9 %
Capacitance (F)	10 pF - 10 mF
Temperature (°C) (type K probe)	-20 °C - +1000 °C
Ambient temperature (°C)	0 °C - 40 °C
Accuracy (%)	0,7 % - 3,0 %
Dimensions	204 x 93 x 57 mm
Weight (gross / net)	946 / 357 g
Required battery(s):	4 x 1,5V AAA
Measuring category (CAT)	CAT III 1000 / CAT IV 600 V



Autorisierter Distributor

TVW Meßtechnik GmbH
Semmelweg 31
32257 Bünde
Fon: 05223 / 9277 - 0
Fax: 05223 / 9277 - 40
info@twvbuende.de
www.twvbuende.de



PAN 188 Video DE:



PAN 188 Video EN:

